

Gauge **13**

ENDUCTION : NITRILE

CUT RESISTANCE GLOVES

The **+**

- Ultra-high cut protection and puncture resistance level
- Excellent abrasion and tear resistance
- Handling cutting parts



DESCRIPTION

Grey knitted support without seams, HPPE and glass fibers, gauge 13.
Black nitrile micro-foam on the palm.

High level of protection against cuts.
Exceptional grip even in wet environment.
Extended shelf life (abrasion resistance 4/4 according to EN 388)
Maximum level of protection for abrasion, tear and puncture resistance (4/4 according to EN 388).
Elastic cuff for higher protection against dirt.
Without seams to avoid irritation hazards.
Not messy colour
Ideal for manipulations of sharp pieces in oily environment.

STANDARD



This glove is in conformity with the model of the individual safety equipment which corresponds to **0075/1747/162/06/16/0642**.
Delivered by CTC (75)

EN420:2003+A1:2009



EN388:2016

A	B	C	D	E
4	3	4	4	D



- Resistance to abrasion (4/4)
- Resistance to blade cut (coupe-test) (3/5)
- Resistance to tear (4/4)
- Resistance to puncture (4/4)
- Resistance to blade cut (TDM) (D/F)

SIZES	REFERENCES
6	1CRLG06
7	1CRLG07
8	1CRLG08
9	1CRLG09
10	1CRLG10
11	1CRLG11

PACKAGING

100 PAIRS / CARTON



X5



X20



APPLICATION DOMAIN



Logistics



Transportation



Maintenance



Building



Wood industry



Glass handling



Waste and recycling



Metal handling

